

LR1000D23 · 905 NM

CLASS-1 D SERIES

LR1000D23

LASER CLASS

CLASS1

IEC 60825-1

Compact Ø23 × 47 mm Class-1 ranging module — 4–1,000 m (vegetation ≥ 750 m, max 1,200 m at night) with IP67 lens cavity, for handheld and mounted electro-optical systems.

MAX RANGE	ACCURACY	WEIGHT	INTERFACE
4–1,000 m (max 1,200 m)	±1 m	≈ 20 g	UART-TTL

TECHNICAL SPECIFICATIONS

FULL SHEET

Laser wavelength	905 nm ± 5 nm
Laser beam divergence	< 6 mrad
Optical material	Resin aspheric lens
Receiver aperture	20 mm ± 0.05 mm
Ranging range	White building: 4–1,000 m (max 1,200 m at night) · vegetation ≥ 750 m
Ranging accuracy	δ ≤ 100 cm, 5 ≤ d < 1,000 m (standard version ±1 m)
Ranging frequency	3–12 Hz (customizable)
Ranging resolution	20 cm typical
Valid measurement rate	≥ 98%
False alarm rate	≤ 1%
Interface	UART-TTL (customizable)
Baud rate	115200 bps
Supply voltage	3.3–5 V (recommended ≥ 3.5 V)
Operating power	Average < 1 W
Average laser power	On request
Response time	On request
Peak / inrush current	≈ 350 mA @ 3.3 V typical
Operating temperature	-20 to +60 °C
Storage temperature	-40 to +60 °C
Protection rating	Lens cavity IP67
Laser safety class	IEC Class 1
Dimensions	Ø23 mm × 47 mm
Spot banding	3.15 × 3.15 cm @ 10 m
Weight	≈ 20 g
Shock / vibration	1000 g/ms (10×/s along optical axis) · 5–50–5 Hz, 2.5 g (also rated 1000 g, 1 ms, 500 cycles)
Reliability	MTBF ≥ 1500 h



INTERFACE

UART-TTL

PIN	SIGNAL	DESCRIPTION
1	GND	Power –
2	VCC	Power +
3	I/O	Reserved for expansion
4	TXD	Module → host
5	RXD	Host → module
6	SW-SHOT	Function enable (active high)

APPLICATION FIT

- HANDHELD OPTICS
- SECURITY
- INDUSTRIAL

Standard 8-byte UART frame (0x55 0xAA header, function code, 4 data bytes, checksum); distance returned ×10 for a one-decimal reading. Full integration manual ships with samples.